

SAFETY DATA SHEET



1025 - INT/EXT POLY SATIN - BLACK


1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	1025 - INT/EXT POLY SATIN - BLACK
Product Code:	1025
Product Use:	Paint

Manufacturer
Richards Paint
200 Paint Street
Rockledge, Florida,
18004320983

24 Hour Emergency Telephone Number
CHEMTEL (US): (800)255-3924
CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Specific Target Organ Toxicity (Repeated Exposure): Category 1 Aspiration Toxicity: Category 1 Flammable Liquid: Category 3 Skin Sensitization: Category 1 Carcinogenicity: Category 2
Signal Word:	Danger
Pictograms:	
Hazard Statements:	H226: Flammable liquid and vapor H304: May be fatal if swallowed and enters airways H317: May cause an allergic skin reaction H351: Suspected of causing cancer H372: Causes damage to organs through prolonged or repeated exposure

Prevention Precautionary Statements:	<p>P201: Obtain special instructions before use</p> <p>P202: Do not handle until all safety precautions have been read and understood</p> <p>P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.</p> <p>P233: Keep container tightly closed</p> <p>P240: Ground/bond container and receiving equipment</p> <p>P241: Use explosion-proof electrical/ventilating/lighting equipment</p> <p>P242: Use only non-sparking tools</p> <p>P243: Take precautionary measures against static discharge</p> <p>P260: Do not breathe dust/fumes/gas/mist/vapors/spray</p> <p>P264: Wash face, hands and any exposed skin thoroughly after handling</p> <p>P270: Do not eat, drink, or smoke when using this product</p> <p>P272: Contaminated work clothing should not be allowed out of the workplace</p> <p>P280: Wear protective gloves/eye protection</p> <p>P281: Use personal protective equipment as required</p>
Response Precautionary Statements:	<p>P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician</p> <p>P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P308+313: IF exposed: Call a POISON CENTER or doctor/physician</p> <p>P333+313: If skin irritation or a rash occurs: Get medical advice/attention</p> <p>P370+378: In case of fire: Use CO2, dry chemical, or foam to extinguish</p> <p>P363: Wash contaminated clothing before reuse</p> <p>P331: Do NOT induce vomiting</p>
Storage Precautionary Statements:	<p>P405: Store locked up</p> <p>P403+235: Store in a well ventilated place. Keep cool.</p>
Disposal Precautionary Statements:	<p>P501: Dispose of contents/container to an approved waste disposal plant</p>
Hazards Not Otherwise Classified:	<p>Objects or materials soaked in this substance may spontaneously ignite if not properly disposed of</p>

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Calcium carbonate	40% to 50%	1317-65-3
Medium aliphatic solvent naphtha (petroleum)	20% to 30%	64742-88-7
Stoddard solvent (mineral spirits)	5% to 10%	8052-41-3
Carbon black	1% to 5%	1333-86-4
Xylene	1% to 5%	1330-20-7
1,2,4-trimethylbenzene	0% to 1%	95-63-6
Ethylbenzene	0% to 1%	100-41-4
Methyl ethyl ketoxime	0% to 1%	96-29-7
Crystalline silica	0% to 1%	14808-60-7

4. FIRST AID MEASURES

General Advice:	Call a physician if symptoms persist. Show SDS to physician.
Eyes:	Immediately flush with water. After initial flushing, remove contact lenses if applicable and continue flushing for at least 15 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.
Skin:	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation:	Move to fresh air. Consult a physician if necessary. If not breathing, give artificial respiration and consult a physician immediately.
Most Important Symptoms/Effects:	May cause allergic skin reaction
Notes to Physician:	Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Foam, dry powder, CO ₂ , water spray. Use measures suitable to the circumstances and environment.
Precautions for Firefighters:	Wear self-contained breathing apparatus and protective gear
Specific Hazards:	Product is combustible. Thermal decomposition may release irritating gases/vapors. Sealed containers may rupture if exposed to high temperatures.
Mechanical Impact Sensitivity:	No
Static Discharge Sensitivity:	Yes

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Remove all sources of ignition. Use proper personal protective equipment. Avoid breathing vapors.
Other Precautions:	If safe to do so, prevent additional spillage. Do not allow material to enter ground water, surface water, or sewer system. Consult local authorities if spillage cannot be contained.
Clean-Up Method:	Soak up with inert absorbent material. Dispose of used absorbent in suitable properly labeled containers. Thoroughly clean contaminated surface.

7. HANDLING AND STORAGE

Handling Precautions:	Wear suitable personal protective equipment. Ground all metal equipment to prevent ignition of vapors by static discharge. Keep away from heat and ignition sources. Do not breathe vapors. Use only in areas with sufficient ventilation.
Storage Precautions:	Keep container properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area. Keep away from heat and ignition sources.
Incompatible Materials:	Strong acids, strong bases, strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

1,2,4-trimethylbenzene(95-63-6)		
ACGIH TWA:	25 ppm	--
NIOSH TWA:	25 ppm	125 mg/m ³
Methyl ethyl ketoxime(96-29-7)		
WEEL TWA:	10 ppm	--
Ethylbenzene(100-41-4)		
ACGIH STEL:	125 ppm	--
ACGIH TWA:	20 ppm	--
NIOSH ST:	125 ppm	545 mg/m ³
NIOSH TWA:	100 ppm	435 mg/m ³
OSHA STEL:	125 ppm	545 mg/m ³
OSHA TWA:	100 ppm	435 mg/m ³
Calcium carbonate(1317-65-3)		
NIOSH TWA:	5 mg/m ³ (respirable fraction)	10 mg/m ³ (total dust)
OSHA PEL:	5 mg/m ³ (respirable fraction)	15 mg/m ³ (total dust)
Xylene(1330-20-7)		
ACGIH STEL:	150 ppm	--
ACGIH TWA:	100 ppm	--
OSHA TWA:	100 ppm	435 mg/m ³
Carbon black(1333-86-4)		
ACGIH TWA:	3 mg/m ³	--
NIOSH TWA:	0.1 mg/m ³	--
OSHA TWA:	3.5 mg/m ³	--
Stoddard solvent (mineral spirits)(8052-41-3)		
ACGIH TWA:	100 ppm	--
NIOSH ceiling (15 min):	--	1800 mg/m ³
NIOSH TWA:	--	350 mg/m ³
OSHA TWA:	500 ppm	2900 mg/m ³
Crystalline silica(14808-60-7)		
ACGIH TWA:	.025 mg/m ³	--
NIOSH TWA:	.05 mg/m ³	--
OSHA TWA:	10 mg/m ³ /%SiO ₂ +2	250 mppcf/%SiO ₂ +5

Engineering Measures:	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
Eye/Face Protection:	Safety glasses/goggles
Skin Protection:	Protective gloves and long-sleeved protective clothing
Respiratory Protection:	NIOSH approved respirator if material is being used in a confined area, is being sprayed, or if exposure limits are exceeded

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Black
Odor:	Little to none
Odor Threshold:	No information available

pH:	No information available
Melting Point (°F):	No information available
Boiling Point (°F):	277.0 -284
Flash Point (°F):	59.00
Flash Point Method:	Closed cup
Evaporation Rate:	No information available
Flammability (Solid/Gas):	No information available
Flammability Limits:	No information available
Vapor Pressure (mm Hg):	No information available
Vapor Density:	No information available
Specific Gravity:	No information available
% Solubility in Water:	No information available
Octanol/Water Partition Coefficient:	No information available
Auto-Ignition Temperature (°F):	No information available
Decomposition Temperature (°F):	No information available
Viscosity (KU):	No information available

10. STABILITY AND REACTIVITY

Reactivity:	Not applicable
Possibility of Hazardous Reactions:	None under normal conditions of use
Hazardous Decomposition Products:	Irritating vapors
Stability:	Stable under normal conditions
Incompatible Materials:	Strong acids, strong bases, strong oxidizing agents
Conditions to Avoid:	Heat, sparks, ignition sources

11. TOXICOLOGICAL INFORMATION

1,2,4-trimethylbenzene(95-63-6)	
Oral LD50 (rat):	6000 mg/kg
Methyl ethyl ketoxime(96-29-7)	
Inhalation LC50 (rat, 4 hrs):	>4.83 mg/L
Oral LD50 (rat):	2326 mg/kg
Subcutaneous LD50 (rat):	2702 mg/kg
Ethylbenzene(100-41-4)	
Dermal LD50 (rabbit):	15433 mg/kg
Oral LD50 (rat):	3500 mg/kg
Carbon black(1333-86-4)	

Dermal LD50 (rabbit):	>3000 mg/kg
Oral LD50 (rat):	>8000 mg/kg
Stoddard solvent (mineral spirits)(8052-41-3)	
Dermal LD50 (rabbit):	>2000 mg/kg
Inhalation LC50 (rat, 4 hrs):	>5 mg/L
Oral LD50 (rat):	>5000 mg/kg
Medium aliphatic solvent naphtha (petroleum)(64742-88-7)	
Dermal LD50 (rat):	>2000 mg/kg
Oral LD50 (rat):	>2000 mg/kg

Primary Routes of Exposure:	Eye contact, skin contact, inhalation
Acute Toxicity:	Repeated or prolonged exposure may to lead to permanent brain and nervous system damage. Inhalation of concentrated vapors may lead to death.

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, dermatitis
Inhalation:	Irritation of respiratory system, headaches, dizziness, drowsiness, unconsciousness
Ingestion:	Irritation of mucous membranes, pulmonary injuries if breathed in during ingestion or vomiting
Target Organ (Single Exposure):	No information available
Target Organ (Repeated Exposure):	No information available
Sensitization:	No information available
Neurological Effects:	No information available
Mutagenicity:	No information available
Reproductive Effects:	No information available
Developmental Effects:	No information available
Other:	No information available

12. ECOLOGICAL INFORMATION

1,2,4-trimethylbenzene(95-63-6)	
Flow-through LC50 (fathead minnow, 96 hrs):	7.72 mg/L
Static EC50 (water flea, 48 hrs):	3.6 mg/L
Methyl ethyl ketoxime(96-29-7)	
BCF:	0.5-0.6
Bioaccumulation (carp, 42 days):	2 mg/L
Semi-static LC50 (Oryzias latipes, 96 hrs):	>100 mg/L
Static EC50 (freshwater algae, 72 hrs):	11.8 mg/L
Static EC50 (water flea, 48 hrs):	201 mg/L
Ethylbenzene(100-41-4)	
Biodegradability (aerobic, 28 days):	70-80%
Flow-through LC50 (Atlantic silverside, 96 hrs):	5.1 mg/L
Static EC50 (Skeletonema costatum, 72 hrs):	4.9 mg/L

Static EC50 (water flea, 48 hrs):	1.8-2.4 mg/L
Carbon black(1333-86-4)	
LC50 (zebra fish, 96 hrs):	>1000 mg/L
Static EC50 (green algae, 72 hrs):	>10000 mg/L
Static EC50 (water flea, 24 hrs):	>5600 mg/L
Stoddard solvent (mineral spirits)(8052-41-3)	
Chronic growth NOELR (aquatic vertebrates):	2.6 mg/L
Chronic reproduction EL50 (water flea):	10 mg/L
Chronic reproduction NOELR (water flea):	2.6 mg/L
Chronic survival NOELR (aquatic vertebrates):	2.6 mg/L
Chronic survival NOELR (water flea):	16 mg/L
EL50 (oncorhynrus mykiss, 48 hrs):	32 mg/L
EL50 (scenedesmus subspicatus, 96 hrs):	45 mg/L
LL50 (oncorhynrus mykiss, 96 hrs):	8.2 mg/L
Medium aliphatic solvent naphtha (petroleum)(64742-88-7)	
LC/EC/IC50 (algae):	>1000 mg/L
LC/EC/IC50 (aquatic invertebrates):	>1000 mg/L
LC/EC/IC50 (fish):	>1000 mg/L

Ecotoxicological Effects:	The environmental impact of this substance has not been fully evaluated
Acute Toxicity to Fish:	No information available
Acute Toxicity to Marine Invertebrates:	No information available
Acute Toxicity to Marine Plants:	No information available
Persistence/Degradability:	No information available
Bioaccumulative Potential:	No information available
Environmental Mobility:	No information available
Ozone:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Empty containers may contain flammable residue and vapors. Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	---

14. TRANSPORT INFORMATION

DOT	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	III
Reportable Quantity:	Xylene, 100 lbs

ICAO/IATA	
Shipping Name:	Paint

Hazard Class:	3
UN No:	1263
Packing Group:	III

IMDG/IMO	
Shipping Name:	Paint
Hazard Class:	3
UN No:	1263
Packing Group:	III

15. REGULATORY INFORMATION

TSCA (US):	All components are listed or exempt
DSL (Canada):	All components are listed or exempt

311/312 Hazard Categories	
Fire:	Yes
Pressure Generating:	No
Reactivity:	No
Acute:	Yes
Chronic:	Yes

SARA 313			
Chemical Name	CAS Number	Max Weight %	de minimis limit
Ethylbenzene	100-41-4	1	0.1
Xylene	1330-20-7	5	1.0


State Right-to-Know					
Chemical Name	CAS Number	MA	NJ	PA	RI
1,2,4-trimethylbenzene	95-63-6	X	X	X	
Ethylbenzene	100-41-4	X	X	X	
Carbon black	1333-86-4	X	X	X	X
Calcium carbonate	1317-65-3	X	X	X	
Xylene	1330-20-7	X	X	X	
Stoddard solvent (mineral spirits)	8052-41-3	X	X	X	X
Crystalline silica	14808-60-7	X	X	X	X
Medium aliphatic solvent naphtha (petroleum)	64742-88-7		X		

California Proposition 65:	This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm
-----------------------------------	---

16. OTHER INFORMATION

HMIS RATING	
Health:	1*
Flammability:	2
Reactivity:	0
Personal Protection:	--

NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 5/26/2016
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.