SAFETY DATA SHEET



4470 - Floor-Tite Acrylic Bonding Primer

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	4470 - Floor-Tite Acrylic Bonding Primer
Product Code:	4470
Product Use:	Primer

Manufacturer Richard's Paint 200 Paint Street Rockledge, Florida,

800-432-0983

24 Hour Emergency Telephone Number

CHEMTEL (US): (800)255-3924 CHEMTEL (International): (813)248-0585

2. HAZARDS IDENTIFICATION

Classification:	
	Communication Standard (29 CFR 1910.1200)
	Skin Sensitization: Category 1
	Carcinogenicity: Category 2
Signal Word:	Warning
Pictograms:	
Hazard	H317: May cause an allergic skin reaction
Statements:	H351: Suspected of causing cancer
Prevention	P201: Obtain special instructions before use
Precautionary	P202: Do not handle until all safety precautions have been read and
Statements:	understood
	P261: Avoid breathing dust/fumes/gas/mist/vapors/spray
	P272: Contaminated work clothing should not be allowed out of the
	workplace
	P280: Wear protective gloves/protective clothing/eye protection/face
	protection
	P281: Use personal protective equipment as required
Response	P302+352: IF ON SKIN: Wash with plenty of water
Precautionary	P308+313: IF exposed: Call a POISON CENTER or doctor/physician
Statements:	P333+313: If skin irritation or a rash occurs: Get medical
	advice/attention
	P363: Wash contaminated clothing before reuse

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 1 of 7

Storage	P405: Store locked up
Precautionary	
Statements:	
Disposal	P501: Dispose of contents/container to an approved waste disposal plant
Precautionary	
Statements:	
Hazards Not	May cause allergic skin reaction
Otherwise	
Classified:	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
2-butoxyethanol	1% to 5%	111-76-2
Di(propylene glycol) butyl ether	1% to 5%	29911-28-2
Texanol ester alcohol	0% to 1%	25265-77-4
Diethylene glycol butyl ether	0% to 1%	112-34-5
Tri(ethylene glycol) bis(2-	0% to 1%	94-28-0
ethylhexanoate)		
Polyethylene glycol tert-	0% to 1%	9036-19-5
octylphenyl ether		
4,4-dimethyloxazolidine	0% to 1%	51200-87-4

4. FIRST AID MEASURES

General Advice:	No hazards requiring special first aid measures
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least
	10 minutes. Keep eyes wide open while flushing. Consult a physician if
	symptoms persist.
Skin:	Remove contaminated clothing. Flush affected area with soap and
	water. Consult a physician if irritation persists. Wash contaminated
	clothing before re-use.
Ingestion:	Remove dentures if applicable and wash out mouth with water. Drink
	large amounts of water. Consult a physician if symptoms persist.
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult
	a physician immediately. Consult a physician if symptoms persist.
Most Important	May cause allergic skin reaction
Symptoms/Effects:	
Notes to Physician:	Treat symptomatically

5. FIRE FIGHTING MEASURES

Suitable	
Extinguishing	
Media:	
Precautions for	Wear self-contained breathing apparatus and protective gear
Firefighters:	
Specific Hazards:	Sealed containers may rupture if exposed to high temperatures

6. ACCIDENTAL RELEASE MEASURES

Personal	Use proper personal protective equipment. Avoid contact with skin,
Precautions:	eyes, and clothing. Avoid breathing vapors.

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 2 of 7

Other Precautions:	If safe to do so, prevent additional spillage	
Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used	
	absorbent in suitable containers.	

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors,
Precautions:	mists, or dust. Wear respiratory equipment if ventilation is insufficient.
Storage	Keep container upright, properly labeled, tightly closed, and out of reach
Precautions:	of children in a cool, dry, well-ventilated area.
Incompatible	None
Materials:	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

2-butoxyethanol(111-76-2)		
ACGIH TWA:	20 ppm	
NIOSH TWA:	5 ppm	24 mg/m3
OSHA TWA:	50 ppm	240 mg/m3
Diethylene glycol butyl ether(112-34-5)		
ACGIH TWA:	10 ppm	

Engineering	Maintain adequate ventilation to keep exposure to airborne
Measures:	contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	No eating, drinking, or smoking while in use. Avoid contact with skin,
	eyes, and clothing. Wash hands, forearms, and face after handling.
	Wash contaminated clothing before re-use.
Eye/Face	Safety glasses/goggles
Protection:	
Skin Protection:	Protective gloves and protective clothing
Respiratory	Respiratory equipment if ventilation is inadequate
Protection:	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Clear
Odor:	Little to none
Odor Threshold:	No information available
pH:	8.5-9.5
Melting Point (°F):	No information available
Boiling Point (°F):	No information available
Flash Point (°F):	215
Flash Point	No information available
Method:	
Evaporation Rate:	No information available
Flammability	No information available
(Solid/Gas):	
Flammability	No information available
Limits:	
Vapor Pressure	No information available
(mm Hg):	
Vapor Density:	No information available
Specific Gravity:	No information available

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 3 of 7

% Solubility in	No information available
Water:	
Octanol/Water	No information available
Partition	
Coefficient:	
Auto-Ignition	No information available
Temperature (°F):	
Decomposition	No information available
Temperature (°F):	
Viscosity (KU):	80-82
Volatile Organic	245.5
Compounds (g/L):	

10. STABILITY AND REACTIVITY

Reactivity:	Not applicable
Possibility of	None under normal conditions of use
Hazardous	
Reactions:	
Hazardous	None under normal conditions of use
Decomposition	
Products:	
Stability:	Stable under normal storage conditions
Incompatible	None
Materials:	
Conditions to	Freezing
Avoid:	

11. TOXICOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)		
	1060 mg/kg	
Dermal LD50 (rabbit):		
Intraperitoneal LD50 (rat):		
Intravenous LD50 (rat):	307 mg/kg	
Oral LD50 (rat):	880 mg/kg	
Di(propylene glycol) butyl ether(29911-28-2)		
Dermal LD50 (rat):	>2,000 mg/kg	
Oral LD50 (rat):	4,000 mg/kg	
Diethylene glycol butyl ether(112-34-5)		
Dermal LD50 (rabbit):	2764 mg/kg	
Oral LD50 (rat):	7291 mg/kg	
Polyethylene glycol tert-octylphenyl ether (9036-19-5)		
Dermal LD50 (rabbit): >3000 mg/kg		
Oral LD50 (rat):	1900-5000 mg/kg	
Texanol ester alcohol(25265-77-4)		
Dermal LD50 (rabbit):	15200 mg/kg	
Oral LD50 (rat):	6500 mg/kg	
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)		
Dermal LD50 (rat):	>2000 mg/kg	
Inhalation LC50 (rat, 4 hrs):	>2 mg/L	
Oral LD50 (rat):	>2000 mg/kg	

Primary Routes of	Eye contact, skin contact, inhalation
Exposure:	
Acute Toxicity:	No information available

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 4 of 7

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, drying
Inhalation:	Irritation of respiratory system
Ingestion:	Gastrointestinal irritation, diarrhea, nausea, vomiting
Target Organ	No information available
(Single Exposure):	
Target Organ	No information available
(Repeated	
Exposure):	
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive	No information available
Toxicity:	
Other:	No information available

12. ECOLOGICAL INFORMATION

2-butoxyethanol(111-76-2)		
Biodegradability (aerobic, 28 days):	90.4%	
Growth inhibition EC50 (green algae, 72 hrs):		
Immobilization EC50 (water flea, 48 hrs):	1550 mg/L	
Static LC50 (rainbow trout, 96 hrs):	1474 mg/L	
Di(propylene glycol) butyl ether(29911-28-2)		
EC50 (Water flea - 48 h)	1,000 mg/l	
LC50 (other fish - 96 h)	841 mg/l	
Diethylene glycol butyl ether(112-34-5)		
Biodegradability (aerobic, 28 days):	91.7%	
LC50 (Pseudomonas putida, 16 hrs):	1170 mg/L	
Static EC50 (Scenedesmus subspicatus, 96 hrs):	>100 mg/L	
Static EC50 (water flea, 48 hrs):	>100 mg/L	
Static LC50 (Lepomis macrochirus, 96 hrs):	1300 mg/L	
Polyethylene glycol tert-octylphenyl ether (9036-19-5)		
IC50 (bacteria, 16 hrs):	5000 mg/L	
LC50 (fathead minnow, 96 hrs):	4-8.9 mg/L	
LC50 (water flea, 48 hrs):	18-26 mg/L	
Texanol ester alcohol(25265-77-4)		
Biodegradability (aerobic, 28 days):		
Static EC50 (green algae, 72 hrs):	18.4 mg/L	
Static EC50 (water flea, 48 hrs):		
Static LC50 (fathead minnow, 96 hrs):	33 mg/L	
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)		
Biodegradability (aerobic, 28 days):	92%	
Static EC50 (green algae, 72 hrs):	>55.9 mg/L	
Static EC50 (water flea, 48 hrs):		
Static LC50 (fathead minnow, 96 hrs):	>97 mg/L	

Ecotoxicological	The environmental impact of this substance has not been fully evaluated	
Effects:		
Persistence/	No information available	
Degradability:		
Bioaccumulative	No information available	
Potential:		

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 5 of 7

Environmental Mobility:	No information available
Other Effects:	No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method:	Dispose of in accordance with federal, state, provincial, and local	
	regulations.	

14. TRANSPORT INFORMATION

DOT:	Not regulated
ICAO/IATA:	Not regulated
IMDG/IMO:	Not regulated

15. REGULATORY INFORMATION

TSCA (US):	All components are listed or exempt
DSL/NDSL	All components are listed or exempt
(Canada):	

311/312 Hazard Categories	
Fire:	No
Pressure	No
Generating:	
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section	
<u>302</u>	
Reportable	This material does not contain any hazardous components listed on
Quantities:	Table 302.4

SARA 313

This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.


State Right-to-Know						
Chemical Name	CAS Number	MA	NJ	PA	RI	
2-butoxythanol	111-76-2	X	Х	X	Χ	
Di(propylene glycol) butyl ether	29911-28-2		Х	Х		
Texanol ester alcohol	25265-77-4		Х	Х		
Diethylene glycol butyl ether	112-34-5		Х	Х		
Tri(ethylene glycol) bis(2-						
ethylhexanoate)	94-28-0		Χ	X		
Polyethylene glycol tert-octylphenyl						
ether	9036-19-5		Χ	X		
4,4-dimethyloxazolidine	51200-87-4		Х	Χ		

California	This product does not contain any materials known to the state of	
Proposition 65:	Proposition 65: California to cause cancer or reproductive harm.	

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 6 of 7

16. OTHER INFORMATION

HMIS RATING	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

Revision Indicator:	Revised 5/7/2018
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in
	good faith and is believed to be accurate as of the effective date listed.
	The information applies only to the product as provided and may not be
	valid if combined with other materials. No warranty is implied or given.
	The user is responsible for complying with all applicable laws and
	regulations.

Date Issued: 5/7/2018 SDS Ref. #: 4470 Page 7 of 7